

POLYTHIOPHENES

BACKGROUND

The invention relates to a process for the preparation of polythiophenes that are soluble or dispersible in anhydrous or low-water-content solvents, to polythiophenes obtainable by this process, and to the use of these polythiophenes.

Organic, conductive polymers have become increasingly widespread in industry. Areas of application are, for example, the through-plating of circuit boards (EP 553 671 A1), the antistatic finishing of photographic films (EP 440 957 A2) or as electrode in solid-electrolyte capacitors (EP 340 512 A2). Particular importance has been achieved by poly-3,4-alkylenedioxythiophenes, which are distinguished by high stability and electrical conductivity.

EP 440 957 A2 describes water-soluble or water-dispersible polyalkylenedioxythiophenes. These are synthesized directly in the presence of polyanions in the aqueous phase. The aqueous preparations are employed for the production of conductive or antistatic coatings. For many applications, however, there is a need for polyalkylenedioxythiophenes which can be processed in the form of anhydrous or low-water-content solutions or dispersions, for example for shortening the drying times of the coatings or for improving the wetting behavior. After removal of the water from the solutions described in EP 440 957 A2, the solids obtained are insoluble in water and organic solvents.

EP 339 340 A2 describes the preparation of 3,4-polyalkylenedioxythiophenes by reaction of the corresponding monomers with oxidants. The 3,4-polyalkylenedioxythiophenes prepared in this way are likewise insoluble in organic and inorganic solvents.

EP 440 957 A2 teaches that the preparation of water-soluble or water-dispersible polyalkylenedioxythiophenes can in principle also be carried out in the presence of protic solvents, such as methanol, ethanol, isopropanol and other water-miscible organic solvents, such as, for

"Express Mail" mailing label number EP671475638US
Date of deposit November 19, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.110 on the date indicated above and is addressed to the Assistant Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Donna J. Veatch
(Name of person mailing paper or fee)

[Signature]
(Signature of person mailing paper or fee)

example, acetone. However, only small amounts of organic solvents can be admixed here, and consequently anhydrous or low-water-content solutions or dispersions cannot be obtained in this way.

Polyalkylenedioxythiophenes are preferably prepared by oxidative
5 polymerization. Known oxidants are transition metals, salt-like compounds and other oxidants. Preference is given here to the use of transition metals and salt-like oxidants, in particular alkali metal or ammonium peroxodisulfates.

Although there have been attempts to use transition metal-contain-
10 ing oxidants, such as iron(III) salts, for the polymerization of thiophenes in organic solvents, such as, for example, chloroform, acetonitrile and methanol, this is afflicted with difficulties and disadvantages. The polythiophenes prepared in this way are not or only partially dispersible in solvents or are only dispersible in solvents with the aid of further dispersion assistants
15 (see in this respect, for example, Lee, S. Park and Y. Son, Mol. Cryst. Liq. Cryst. 327 (1999) 237-240). The transition metal-containing residues of the oxidants can only be removed from the reaction solutions with difficulty and have an adverse effect on the quality of the conductive or antistatic coatings, such as, for example, their ageing resistance.

20 Salt-like oxidants, such as peroxodisulfate or perborates, and other salt-like compounds only react very slowly if at all in the absence of water or in the presence of only small amounts of water, giving rise to unacceptably long reaction times when the reaction is carried out in low-water-content solvents. The reaction solutions obtainable in this way contain
25 large amounts of monomers and virtually no polythiophenes and therefore cannot be used.


Surprisingly, it has now been found that polythiophenes of high quality that are readily soluble or dispersible in anhydrous or low-water-content solvents can be prepared if these are prepared in anhydrous or
30 low-water-content solvents and phase-transfer catalysts are added during the reaction. The preparation process has the advantage that it is possible to prepare solvent-containing anhydrous or low-water-content

polythiophene dispersions or solutions that have only low metal and salt contents after work-up. The polythiophenes prepared by the process according to the invention are stable on storage as a solid, dispersion or solution and are suitable for the production of conductive or antistatic

5 layers of high quality.

SUMMARY

The invention relates to a process for preparing polythiophenes comprising (1) reacting (a) one or more thiophenes of the general formula (I)



wherein R^1 is an unsubstituted or substituted alkylene or an alkenylene radical having from 1 to 10 carbon atoms, and R and R^2 ,
 15 independently of one another, are hydrogen, a linear or branched alkyl radical having from 1 to 20 carbon atoms, OH, $O-CH_2-CH_2-CH_2-SO_3H$ or O-alkyl having 1-18 carbon atoms, (b) at least one compound containing one or more sulfonic acid groups, (c) at least one oxidant, (d) at least one phase-transfer catalyst, and (e) optionally one or more catalysts,
 20 with (f) at least one anhydrous or low-water-content solvent at a temperature ranging from 0 to about $150^\circ C$, thereby forming a product, and (2) subsequently working up the product. The invention also relates to a polythiophene made with such a process as well as a conductive coating or an anti-static coating made with such a polythiophene. These and other
 25 features, aspects, and advantages of the present invention will become better understood with reference to the following description and appended claims.


DESCRIPTION

With the same chemical composition, the polythiophenes according to the invention surprisingly differ significantly from polythiophenes prepared in accordance with the state of the art. The polythiophenes according to the invention dissolve spontaneously in solvents and also water, even in high concentrations, without precipitations, swelling or other undesired effects, such as, for example, an increase in the viscosity, occurring.

This was surprising and unforeseeable for the person skilled in the art since the person skilled in the art had to assume that the polymerization reaction of identical thiophene starting materials using the identical oxidant should lead to products having known properties, and the addition of phase-transfer catalysts should merely increase the reaction rate during the polymerization. However, this is not the case. The polythiophenes according to the invention dissolve spontaneously in water and organic solvents.

The invention therefore relates to a process for the preparation of polythiophenes in which

a) one or more thiophenes of the general formula (I)



in which R^1 is an unsubstituted or substituted alkylene or alkenylene radical having from 1 to 10 carbon atoms, and


R and R^2 , independently of one another, are hydrogen, a linear or branched alkyl radical having from 1 to 18 carbon atoms, OH , $O-CH_2-CH_2-CH_2-SO_3H$ or O -alkyl having 1-18 carbon atoms,

- a) at least one compound containing one or more sulfonic acid groups,
 b) at least one oxidant,
 c) at least one phase-transfer catalyst, and
 5 d) if desired one or more catalysts,
 are reacted in at least one anhydrous or low-water-content solvent at temperatures of from 0 to 150°C, and the product is subsequently worked up.

The invention also relates to the polythiophenes that can be prepared
 10 by this process.


Finally, the invention relates to the use of the polythiophenes prepared in accordance with the invention, for example in the form of solids, dispersions or solutions, for the production of conductive and/or antistatic coatings and moldings.

15 The process according to the invention is preferably carried out using thiophenes of the general formula (II) or (III)



(II)

or




(III)

20 where

R^3 , R^4 , R^5 , R^6 , R^7 and R^8 are each, independently of one another, a hydrogen atom, an alkyl group having from 1 to 20 carbon atoms, a hydroxymethyl group, or an alkoxymethyl group ($R-O-CH_2-$) having
 25 from 1 to 20 carbon atoms which is unsubstituted or substituted by sulfonic acid groups.

The thiophenes employed in the process according to the invention are particularly preferably thiophenes of the general formula (IV)



5

where

R^9 is hydrogen or an alkyl radical having from 1 to 20 carbon atoms.

Very particularly suitable thiophenes which may be mentioned are the following: 3,4-methylenedioxythiophene, 3,4-ethylenedioxythiophene, 3,4-propylenedioxythiophene, thiophenes carrying hydroxyl or alkoxy groups, as described, for example, in US-A-5,111,327, and thiophenes carrying $[-CH_2-O-(CH_2)_n-SO_3H]$ groups.

Suitable compounds containing one or more sulfonic acid groups are compounds that carry at least one sulfonic acid linked to an aliphatic, cycloaliphatic or aromatic carbon atom. These are preferably polysulfonic acids, for example polystyrenesulfonic acids and polyvinylsulfonic acids having a molecular weight (Mw) of from 2000 to 2,000,000, preferably from 5000 to 500,000, toluenesulfonic acids, benzenesulfonic acids, which may carry alkyl radicals having from 1 to 20 carbon atoms, for example dodecylbenzenesulfonic acid, alkylsulfonic acids having from 1 to 20 carbon atoms, for example methanesulfonic acid and laurylsulfonic acid. However, it is also possible, if desired, to use or additionally use compounds which carry an $[-O-SO_2-OH]$ group (i.e. sulfuric acid monoesters).

Preferred oxidants are salt-like oxidants, preferably peroxodisulfates, for example alkali metal and ammonium peroxodisulfate, and percarbonates, such as alkali metal percarbonate.

Polythiophenes are prepared in accordance with the invention in the presence of a phase-transfer catalyst. Phase-transfer catalysts increase the solubility of the oxidants in the solvent. Examples of suitable phase-transfer catalysts are either compounds which complex alkali metal ions or are ionic compounds containing long-chain alkyl radicals which have a counterion which is soluble in the solvent and thus increase the solubility of the oxidants. Preferred phase-transfer catalysts are compounds containing $-CH_2-$ and $-O-$ structural units, for example crown ethers, such as, for example, 12-crown-4 or 18-crown-6, benzo- or dibenzo-18-crown-6, or polyethers prepared from ethylene oxide. Preference is likewise given to quaternary ammonium salts, particularly preferably quaternary ammonium salts containing alkyl radicals or arylalkyl radicals having from 4 to 20 carbon atoms, such as, for example, butyl-, decyl-, lauryl- or benzyltrimethylammonium salts, and corresponding phosphorus compounds.

If desired, one or more catalysts that increase the rate of polymerization are added in the process according to the invention. Examples of suitable catalysts are iron(III) or other transition-metal compounds, such as, for example, manganese salts. Examples which may be mentioned are iron(III) chloride, iron(III) sulfate, iron(III) toluenesulfonate, manganese dioxide and manganese(II) salts.

The process according to the invention is carried out in an anhydrous or low-water-content solvent. Suitable solvents are those which contain up to about 5% by weight of water. These solvents preferably contain less than about 2% by weight of water.

Suitable anhydrous or low-water-content solvents are in principle organic solvents. These are, for example, alcohols, for example methanol, ethanol, propanol, butanol, pentanol or higher alcohols, ethylene glycol, diethylene glycol, triethylene glycol or higher homologues, ketones, such as, for example, acetone or butanone, chlorinated hydrocarbons, for example methylene chloride, chloroform, tetrachloromethane, dichloroethane or trichloroethane, aromatic compounds, such as, for

example, toluene, xylene, chlorobenzene or dichlorobenzene, aliphatic or cycloaliphatic hydrocarbons, such as, for example, pentane, hexane, heptane, cyclohexane and octane, ethers, such as, for example, tetrahydrofuran, diethyl ether, methyl tert-butyl ether, ethylene glycol

5 mono- or dimethyl ether or higher homologues thereof, amides, such as, for example, dimethylformamide, dimethylacetamide or N-methylpyrrolidone, and esters, such as, for example, ethyl or butyl acetate.

The anhydrous or low-water-content solvents are preferably lower alcohols having from 1 to 8 carbon atoms, preferably methanol, ethanol,

10 propanol, isopropanol, butanol and/or pentanol.

The process according to the invention is usually carried out by reacting, per mole of thiophene employed or mixture of a plurality of thiophenes employed, from about 0.1 to about 20 mole equivalents, preferably from about 0.2 to about 10 mole equivalents, particularly preferably

15 from about 0.5 to about 5 mole equivalents, of sulfonic acid groups of the compound containing sulfonic acid groups, from about 0.9 to about 5.0 mole equivalents, preferably from about 1.0 to about 3.0 mole equivalents, particularly preferably from about 1.1 to about 2.0 mole equivalents, of the oxidant, where one equivalent of oxidant is capable of taking up two moles

20 of electrons, from about 0.1 to about 10 mol%, preferably from about 1 to about 5 mol%, of phase-transfer catalyst, based on the oxidant, from 0 to about 10 mol% of catalyst (other than the phase-transfer catalyst), based on thiophene, and solvent in such an amount that the ratio between thiophene and solvent is from about 0.001 to about 0.1:1, at a temperature

25 ranging from 0 to about 150°C, preferably from about 15 to about 70°C, particularly preferably from about 20 to about 40°C, and subsequently working up the reaction product.

The work-up preferably consists of the removal of ions remaining in the reaction mixture, i.e. preferably desalination. However, possible

30 undesired secondary components can also be removed from the reaction solution during the work-up.

Possible work-up steps are, for example, filtration or decantation of the reaction solution, precipitation, washing and drying of the polythiophene and further purification steps which are usual and are known to the person skilled in the art. In many cases, however, it is advisable additionally to remove salts with the aid of ion exchanger resins known to the person skilled in the art or other special methods for selective removal of ions, for example with the aid of ion-selective membranes.

The polythiophenes prepared by the process according to the invention are stable on storage as a solid, dispersion or solution. The polythiophenes according to the invention can be used as dispersions or solutions for the preparation of electrically conductive or antistatic coatings. Suitable areas of application are the finishing of plastic films for the packaging of electronic components and for clean-room packaging, antistatic finishing of cathode ray tubes, antistatic finishing of photographic films, as transparent electrodes, for example for touch screens and organic or inorganic electroluminescent displays, for the production of capacitors, batteries, circuit boards or window panes which can be colored electrically.

Before production of the coatings, it is possible to add binders and/or crosslinking agents, such as polyurethanes or polyurethane dispersions, polyolefin dispersions, epoxysilanes, such as 3-glycidoxypolytrialkoxysilane, to the polythiophene dispersions according to the invention. Furthermore, silane hydrolysates, for example based on tetraethoxysilane, can be added in order to increase the scratch resistance in coatings.

The coatings can be produced by known processes, such as spraying, gravure printing, offset printing, curtain coating, application via application rolls and brushing.

The invention is further described in the following illustrative examples in which all parts and percentages are by weight unless otherwise indicated.

EXAMPLES

EXAMPLE 1 (Preparation of an Ethanolic Polystyrenesulfonic Acid Solution)

- 400 ml of an aqueous solution of a polystyrenesulfonic acid having a
- 5 molecular weight (Mw) of about 70,000 were evaporated to dryness and dissolved in 1000 ml of ethanol. The solids content of the solution was found to be 10.4% by weight.

EXAMPLE 2 (Preparation of a Polythiophene According to the Invention in the Form of a Solution)

- 10 133 ml of ethanol, 14.77 g (0.0256 mol) of iron(III) toluenesulfonate, 1399.76 g of the polystyrenesulfonic acid solution from Example 1, 3.7 g (0.014 mol) of 18-crown-6, 74.66 g (0.2765 mol) of potassium peroxodisulfate and 27.97 g (0.1967 mol) of 3,4-ethylenedioxythiophene were combined in a reactor and homogenized for 1 minute using a commercially
- 15 available disperser (Ultra-Turrax[®] from IKA). A finely divided suspension was formed. The suspension was subsequently stirred at room temperature for 24 hours. The reactor contents became a dark-blue color during the reaction time. The reaction conversion was found to be 95.1% by analysis by gas chromatography.

- 20 EXAMPLE 3 (Purification of a Polythiophene According to the Invention)

- The solution from Example 2 was filtered, 455 ml of cation exchanger (Lewatit[®] S 100, a strongly acidic ion exchanger containing sulfonate groups based on crosslinked polystyrene, commercial product from Bayer AG, Leverkusen) and 525 ml of anion exchanger (Lewatit[®] MP 62, a basic
- 25 ion exchanger containing tertiary amino groups based on crosslinked polystyrene, commercial product from Bayer AG, Leverkusen) were added, and the mixture was stirred for 1 hour and filtered. A dark-blue, clear solution was obtained. A sample of this solution was diluted with ethanol to a solids content of 0.4% by weight, and a coating with a
- 30 thickness of 60 μm was applied from the dilute solution to a plastic film (polyethylene terephthalate) with the aid of a hand coater and dried at 80°C for 15 minutes. The thickness of the dry coating was about 240 nm.

The surface resistance of the applied layer was 7 Mohm/square in accordance with IEC standard 93 (VDE 0303 Part 30) or ASTM D 257.

EXAMPLE 4 (Purification and Isolation of the Polythiophene According to the Invention)

- 5 A polythiophene solution was prepared as described in Example 2. The solution was filtered. 1500 ml of toluene were added to 1000 ml of the polythiophene solution with stirring, and the mixture was stirred for a further 15 minutes. A dark-blue precipitate was obtained, from which the clear supernatant liquid was decanted. The residue was washed twice with
- 10 100 ml of toluene each time, dried and powdered, giving 97 g of dark-blue/black powder.

EXAMPLE 5 (Preparation of a Solution of the Polythiophene According to the Invention in Ethanol)

- 15 10 g of the polythiophene powder from Example 4 were stirred in 90 ml of ethanol for 30 minutes. A dark-blue clear solution was obtained. The solution was filtered through a 0.2 μ m filter. No filtration residue was obtained. The particle size distribution of the solution was measured by means of light scattering in an ultracentrifuge. The mean particle size was about 30 nm (d50).

- 20 A coating with a thickness of approximately 240 nm was produced from the solution as described in Example 3. The surface resistance of the applied layer was 6.7 Mohm/square in accordance with IEC standard 93 (VDE 0303 Part 30) or ASTM D 257.

- 25 EXAMPLE 6 (Preparation of a Solution of the Polythiophene According to the Invention in Water)

- 30 10 g of the polythiophene powder from Example 4 were stirred in 90 ml of water for 30 minutes. A dark-blue clear solution was obtained. The solution was filtered through a 0.2 μ m filter. No residue was obtained. The particle size distribution of the solution was measured by means of light scattering in an ultracentrifuge. The mean particle size was about 30 nm (d50).

A coating with a thickness of approximately 240 nm was produced from the solution as described in Example 3. The surface resistance of the applied layer was 5.2 Mohm/square in accordance with IEC standard 93 (VDE 0303 Part 30) or ASTM D 257.

5 COMPARATIVE EXAMPLE 1 (Repetition of Example 2 Without Phase-Transfer Catalyst)

133 ml of ethanol, 14.77 g (0.0256 mol) of iron(III) toluenesulfonate, 1399.76 g of the polystyrenesulfonic acid solution from Example 1, 74.66 g (0.2765 mol) of potassium peroxodisulfate and 27.97 g (0.1967 mol) of 3,4-ethylenedioxythiophene were combined in a reactor and homogenized for 1 minute using a commercially available disperser (Ultra-Turrax® from IKA). A finely divided suspension was formed. The suspension was subsequently stirred at room temperature for 24 hours. The reactor contents did not change color during the reaction time. After a reaction time of one week, the contents were slightly greenish. The reaction conversion was found to be 2.5% by analysis by gas chromatography.

Comparative Example 1 shows that without addition of phase-transfer catalysts, an adequate reaction rate is not achieved and virtually no polythiophene is obtained.

20 COMPARATIVE EXAMPLE 2 (Repetition of Example 2 in Water)

724 g of water, 14.77 g (0.0256 mol) of iron(III) toluenesulfonate, 808.75 g of a polystyrenesulfonic acid solution in water (Mw about 70,000 g/mol, 18% strength by weight in water), 3.7 g (0.014 mol) of 18-crown-6, 74.66 g (0.2765 mol) of potassium peroxodisulfate and 27.97 g (0.1967 mol) of 3,4-ethylenedioxythiophene were combined in a reactor and homogenized for 1 minute using a commercially available disperser (Ultra-Turrax® from IKA). A milky dispersion was formed which became a blue color after a few minutes. The dispersion was subsequently stirred and homogenized at room temperature for 24 hours. A highly viscous suspension containing coarse gel particles was formed. The gel particles were insoluble in ethanol.

The comparative example shows that the same reaction in water leads to a polythiophene which differs significantly in solubility from the polythiophene according to the invention.

COMPARATIVE EXAMPLE 3 (Preparation of a Polythiophene of the

- 5 Same composition as in Example 2 of EP 440957 A2 in water, but with a lower Solids Content)

- 1588.13 g of water, 15.08 g of a 1 per cent strength by weight aqueous iron(III) sulfate solution, 359.79 g of a polystyrene sulfonic acid solution in water (Mw about 70,000 g/mol, 5.5% strength by weight in water) and 8.02 g (0.056 mol) of 3,4-ethylenedioxythiophene were introduced into a reactor at room temperature and homogenized for 15 minutes using a commercially available disperser (Ultra-Turrax® from IKA). A milky suspension was formed. 19.24 g (0.081 mol) of sodium peroxodisulfate were added. After 10 minutes, the solution became a blue color. The dispersion was subsequently stirred and homogenized at room temperature for 24 hours. A dark-blue, slightly viscous solution was formed. 106.65 g of cation exchanger (Lewatit® S 100, a strongly acidic ion exchanger containing sulfonate groups based on crosslinked polystyrene, commercial product from Bayer AG, Leverkusen) and 160.6 g of anion exchanger (Lewatit® MP 62, a basic ion exchanger containing tertiary amino groups based on crosslinked polystyrene, commercial product from Bayer AG, Leverkusen) were added to this solution, and the mixture was stirred for 30 minutes. The ion exchanger was subsequently filtered off through an 8 µm filter. As described in Example 3, a coating with a thickness of approximately 240 nm was produced from the solution. The surface resistance of the applied layer was 2.5 Mohm/square in accordance with IEC standard 93 (VDE 0303 Part 30) or ASTM D 257.

10 ml of the solution were dried and powdered. The resultant powder was not soluble in either water or ethanol.

- 30 The comparative example shows that aqueous polythiophene solutions can be prepared in accordance with the prior art, but they differ in solubility from the polythiophenes according to the invention.

Although the present invention has been described in detail with reference to certain preferred versions thereof, other variations are possible. Therefore, the spirit and scope of the appended claims should not be limited to the description of the versions contained therein.

0
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220